

TODAY



NEW



Among the many **MODELS** on the **MARKET**, choose

“K. 800 H.V.”

THE BEST EVOLUTION OF THAT EXPERIENCE !

**ELECTROSTATIC[®]
SPRAY SYSTEM**

Technical specifications:

1 Cylinder/2 Strokes - 72,4 cc engine - 3.7 kW (5cv) - 6700 revs/min - Manual recoil starter - Electronic IGNITION - fan's AIR VOLUME 1,044 Cu.m./h (36,874.08 cubic feet/h.) - AIR SPEED 120 m/s (393,60 feet/s.) - FUEL TANK 1.7 l (0,45 USG) - CHEMICAL MIX TANK 14 l (3,7 USG) - 4 positions FLUID DOSING DEVICE - multifunctional ergonomic JOYSTICK with: stop - accelerator - fluid release opening - double safety for gases and fluids - EMPTY WEIGHT 12 Kg. (26.52 lbs) - SPRAY SWATH: vertical 8 m (27') - horizontal 10/12 m (33' to 40').



MARTIGNANI s.r.l.
Via Fermi, 63 - Zona Industriale Lugo 1
48020, S. Agata sul Santerno (RA) Italy
Tel. (+39) 0545.230.77 Fax (+39) 0545.306.64
e-mail: martignani@martignani.com

NEW

Optional: ELECTROSTATIC SYSTEM